Rex LITE is the dual-frequency pipe & cable locator for all utilities

A high-performance locator that's lighter on the wallet and lighter to carry, but no lightweight in the field.



Optimized for finding

- Water, sewer, and gas pipes
- Electric & telecomm cables









ULTRA LIGHTWEIGHT • DIRECTIONAL ARROWS • EXTENDS & RETRACTS

Audio + Visual Display

Audio signals and directional arrows help pinpoint underground targets.







Receiver Specifications			
Operating Frequency:	Active: 33 kHz and 512 Hz (33kHz model), 82 kHz and 512 Hz (82 kHz model); Passive: 50 or 60 Hz; Sonde: 512 Hz		
Battery:	One 9V Battery		
Battery Life:	12 Hours (intermittent usage)		
Weight (incl. battery):	2.8 lbs (1.25 kg)		
Operating Temperature:	-4°F to 140°F (-20°C to 70°C)		
Overall Dimensions:	Closed: 17.5" (44 cm); Extended: 27.7" (70 cm)		
Max. Depth Capability:	Approximately 19' (5.8 m)		
	Sonde mode - approximately 5' - 15' (1.5 m to 4.2 m)		
Water and Dust Resistance:	Rated IP54		

1		
		-1
l i un	41	0.5
1 =	9.1	1000
hilli	dllu	2
TUILLE	offlia	



Slim, Sleek & Powerful Transmitter 3.44 lbs and 1.75" thick

Transmitter Specifications		
Operating Frequency:	33 kHz and 512 Hz (33 kHz model); 82 kHz and 512 Hz (82 kHz model)	
Operating Modes:	Conductive, all frequencies; Inductive, 33 kHz or 82 kHz only; Inductive Clamp (optional), 33 kHz or 82 kHz only	
Max. Output Power:	Conductive mode, 33 kHz and 512 Hz - 1 W Max @ 1000 Ω load; 82 kHz - 1/2 W or 1 W (FCC limited)	
Battery Type:	10 AA Alkaline (1.5 V nominal)	
Battery Life:	8 Hours (intermittent usage)	
Dimensions:	10"W x 10.25"D x 1.75"H (25.4 cm x 26 cm x 4.5 cm)	
Weight (incl. batteries):	3.44 lbs (1.56 kg)	
Operating Temp.:	-4°F to 140°F (-20°C to 70°C)	
Water and Dust Resistance:	Rated IP54	





Copyright © 2019 Schonstedt Instrument Company. All rights reserved. Schonstedt is a subsidiary of SPX Corporation. Due to a policy of continued development, we reserve the right to alter or amend any published specification without notice. This document may not be copied, reproduced, transmitted, modified or used, in whole or in part, without the prior written consent of Schonstedt Instrument Company.

SCHONSTEDT°

Contact Us:

Find Your Local Dealer:

800-999-8280 schonstedt.info@spx.com

schonstedt.com